



V/5 123 MM Ø
(Suitable for 150 mm Bore Dia.)

A part of your family....

Regular Noryl Series

Performance At Rated Voltage i.e. 415v, 50Hz, Ac Supply.

MODEL NO.	H.P.	STAGE	OUTLET	PHASE	DISCHARGE IN L.P.M.						
						35	45	65	85	105	125
KMP-190	3	15	1.5	3ø	HEAD IN METERS.	108	104	94	75	54	31
KMP-191	5	27	1.5	3ø		195	188	170	135	98	56
KMP-192	6	32	1.5	3ø		230	222	200	160	116	66
KMP-193	7.5	40	1.5	3ø		288	242	250	200	145	82
KMP-194	10	45	1.5	3ø		318	291	277	231	161	94
MODEL NO.	H.P.	STAGE	OUTLET	PHASE	DISCHARGE IN L.P.M.						
						75	85	95	105	125	135
KMP-195	3	12	1.5	3ø	HEAD IN METERS.	80	78	75	70	55	38
KMP-196	5	22	1.5	3ø		148	142	138	130	105	78
KMP-197	6	27	1.5	3ø		178	172	168	161	130	92
KMP-198	7.5	32	1.5	3ø		215	207	200	192	165	120
KMP-199	10	40	1.5	3ø		314	263	251	240	221	165
MODEL NO.	H.P.	STAGE	OUTLET	PHASE	DISCHARGE IN L.P.M.						
						95	115	125	135	150	170
KMP-200	3	10	2	3ø	HEAD IN METERS.	75	70	65	60	45	35
KMP-201	5	16	2	3ø		116	110	102	96	80	65
KMP-202	6	22	2	3ø		160	151	140	131	110	89
KMP-203	7.5	25	2	3ø		178	170	160	150	125	98
KMP-204	10	28	2	3ø		196	189	178	165	140	112
MODEL NO.	H.P.	STAGE	OUTLET	PHASE	DISCHARGE IN L.P.M.						
						120	160	175	190	225	275
KMP-205	3.00	8	2.0	3ø	HEAD IN METERS.	58	55	51	46	40	28
KMP-206	5.00	12	2.0	3ø		90	84	78	72	60	48
KMP-207	6.00	16	2.0	3ø		115	110	108	95	80	55
KMP-208	7.50	20	2.0	3ø		145	136	128	121	100	75
KMP-209	10.00	25	2.0	3ø		185	169	158	150	125	100
MODEL NO.	H.P.	STAGE	OUTLET	PHASE	DISCHARGE IN L.P.M.						
						580	510	480	460	350	250
KMP-211	3.00	3	2.50	3ø	HEAD IN METERS.	20	21	22	23	25	26
KMP-212	5.00	5	2.50	3ø		34	36	37	39	41	44
KMP-213	6.00	6	2.50	3ø		40	43	44	47	49	53
KMP-214	7.50	8	2.50	3ø		54	57	58	62	66	70
MODEL NO.	H.P.	STAGE	OUTLET	PHASE	DISCHARGE IN L.P.M.						
						600	550	520	490	390	275
KMP-215	3.00	4	2.50	3ø	HEAD IN METERS.	27	28	29	29	33	35
KMP-216	5.00	6	2.50	3ø		40	43	44	44	49	53
KMP-217	6.00	8	2.50	3ø		54	57	58	58	66	70
KMP-218	7.50	10	2.50	3ø		67	71	73	73	82	85